Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-467-0981

# Thread Class:

32

**Thread Direction:** 

**Right-hand** 

# Thread Length:

0.218 inches

### Fastener Length:

0.218 inches

#### Head Diameter:

0.250 inches

Head Height:

#### 0.125 inches

Internal Drive Style:

Slot

#### End Application:

Fighting vehicle systems, bradley

### **Thread Diameter:**

0.164 inches

### Thready Qty Per Inch (tpi):

32

## **Special Features:**

All edges and corners shall be free of burs; finish: glass bead peen blast iaw mil-std-852, copper plate iaw mil-c-14550, class4, electroless nickel plate iaw mil-c-26074, class 4, rade b; all fillet radii shown as sharp edges shall be .015 in max; workmanship in accordance with mil-hdbk-454, guideline9; armored reconnaisance-airborne assa.

Material:

Stainless steel

## Material Specification:

Qq-s-763; type303 federal specification single material response

#### **Thread Series Designator:**

Unc

## Shelf Life:

N/a

## Unit Of Measure:

```
---
```

#### Demilitarization:

No

Fiig:

A003b0

### Mil-std (military Standard):

Mil-std-852 spec.