NSN 5305-01-467-6664

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-467-6664 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.3630 inches **Fastener Length:** Between 1.149 inches and 1.179 inches **Head Style:** Flat countersunk **Head Diameter:** 0.3813 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **End Application:** C-17a aircraft **Thread Diameter:** 0.1900 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Point of screw shall be flat and chamfered; heat treat 160-180 ksi ftu per ams 4928 or ams 4967; the offset cruciform recess diameter is 0.248 inch Material: Titanium alloy uns r54520 **Material Specification:** Ams4928 assn standard 1st material response or ams4967 assn standard 2nd material response **Thread Series Designator:** Unjf Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-01-467-6664

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0