

View Online at <https://aerobasegroup.com/nsn/5305-01-467-7063>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.362 inches

Fastener Length:

Between 0.674 inches and 0.714 inches

Head Style:

Hexagon

Head Height:

Between 0.109 inches and 0.141 inches

Width Between Flats:

Between 0.365 inches and 0.377 inches

Shoulder Diameter:

0.186 inches first shoulder and 0.189 inches first shoulder

Shoulder Length:

0.322 inches first shoulder

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.1380 inches

Thready Qty Per Inch (tpi):

32

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or ams 6300 assn standard all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.