NSN 5305-01-467-7197

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-467-7197 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.531 inches **Fastener Length:** 2.719 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.491 inches and 0.507 inches **Internal Drive Style:** Cross recess type ii **End Application:** 1520-01-088-5669 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 62000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-430 federal specification single material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625, type i or ii military specification single treatment response **Special Features:** The screw diameter is 0.246 inch min. And 0.249 inch max.; head height is 0.106 inch; used on the cargo-transport helicopter, chinook ch-47 **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-467-7197

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.