

View Online at <https://aerobasegroup.com/nsn/5305-01-467-7474>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.438 inches

**Fastener Length:**

Between 1.361 inches and 1.391 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.490 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**End Application:**

C-17a aircraft

**Thread Diameter:**

0.3125 inches

**Grip Length:**

Between 0.928 inches and 0.948 inches

**Thready Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Item has drilled shank at the threaded end, and the distance from end to shank hole center is 0.172 inch min., 0.192 inch max; the diameter of the hole is 0.076 inch min., 0.086 inch max.

**Material:**

Stainless steel

**Material Specification:**

Ams 5731 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0