NSN 5305-01-467-8860

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-467-8860 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.177 inches **Fastener Length:** 0.500 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **First Diameter From Head:** Between 0.070 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.323 inches **Internal Drive Style:** Hexagon **End Application:** Bradley **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 **Externally Relieved Body Diameter Quantity: Special Features:** Altered from ms16995-11 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Unc

Thread Series Designator:

NSN 5305-01-467-8860

Externally Relieved Body Screw - Page 2 of 2



Sneit	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0