## NSN 5305-01-467-9960

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-467-9960

Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.406 inches

#### Fastener Length:

3.156 inches

#### Head Style:

Flat countersunk

#### Head Diameter:

Between 0.375 inches and 0.387 inches

Internal Drive Style:

## Cross recess type ii

**End Application:** 

#### Hc130n nvis, hercules c130

Thread Diameter:

0.190 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

#### **Countersink Angle:**

100.0 degrees

#### Screw Material:

Steel comp 4130 or steel comp 4340 or steel comp 8740

#### Screw Material Specification:

Mil-s-6758 military specification single material response or mil-s-5000 military specification single material response or mil-s-6049 military

specification single material response

## Screw Surface Treatment:

Cadmium

#### Screw Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

#### Thread Series Designator:

Unjf

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5305-01-467-9960

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-6758 spec.

