

View Online at <https://aerobasegroup.com/nsn/5305-01-468-0821>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.641 inches

Fastener Length:

0.641 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.752 inches and 0.762 inches

Single Shear Strength:

10500 pounds per square inch

Internal Drive Style:

Cross recess type iii

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

12700 pounds per square inch

Thread Pitch In Millimeters:

9.0

External Thread Tolerance Class:

3a

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-8844 military specification 2nd material response or mil-s-6049 military specification 3rd material response or ams6014 assn standard 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, typeii, class3 federal specification 1st treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.