NSN 5305-01-468-9141

Close Tolerance Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-01-468-9141 | | | | | | |
|---|--|--|--|--|--|--|
| Thread Class: | | | | | | |
| 3a | | | | | | |
| Thread Direction: | | | | | | |
| Right-hand | | | | | | |
| Thread Length: | | | | | | |
| 0.312 inches | | | | | | |
| Fastener Length: | | | | | | |
| Between 1.282 inches and 1.312 inches | | | | | | |
| Head Style: | | | | | | |
| Flat countersunk | | | | | | |
| Head Diameter: | | | | | | |
| Between 0.438 inches and 0.445 inches | | | | | | |
| Spline Minor Diameter: | | | | | | |
| 0.1570 inches | | | | | | |
| Spline Major Diameter: | | | | | | |
| 0.1600 inches | | | | | | |
| Grip Diameter: | | | | | | |
| 0.312 inches | | | | | | |
| Internal Drive Style: | | | | | | |
| Torx | | | | | | |
| End Application: | | | | | | |
| Used on fighter aircraft (f18-e/f) | | | | | | |
| Thread Diameter: | | | | | | |
| 0.312 inches | | | | | | |
| Grip Length: | | | | | | |
| 1.000 inches | | | | | | |
| Thready Qty Per Inch (tpi): | | | | | | |
| 24 | | | | | | |
| Countersink Angle: | | | | | | |
| Between 99.0 degrees and 101.0 degrees | | | | | | |
| Criticality Code Justification: | | | | | | |
| Agav | | | | | | |
| Product Name: | | | | | | |
| Bolt 100 degree reduced head, gear drive recess-special thread length, ph13-8mo (125 ksi shear) | | | | | | |
| Material: | | | | | | |
| Stainless steel | | | | | | |
| Surface Treatment: | | | | | | |
| Aluminum | | | | | | |
| Thread Series Designator: | | | | | | |
| Unjf | | | | | | |
| Shelf Life: | | | | | | |
| N/a | | | | | | |

NSN 5305-01-468-9141

Close Tolerance Screw - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0