## NSN 5305-01-468-9560

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-468-9560

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.354 inches and 0.425 inches                       |
| Fastener Length:  |
| Between 0.735 inches and 0.765 inches                       |
| Head Style:   |
| Flat countersunk  |
| Head Diameter:  |
| Between 0.477 inches and 0.507 inches                       |
| Spline Major Diameter:                                      |
| 0.221 inches  |
| Grip Diameter:  |
| Between 0.2490 inches and 0.2495 inches                     |
| Single Shear Strength:                                      |
| 125000 pounds per square inch                               |
| Internal Drive Style:                                       |
| Torx  |
| Thread Diameter:  |
| 0.250 inches  |
| Grip Length:  |
| Between 0.315 inches and 0.335 inches                       |
| Thready Qty Per Inch (tpi):                                 |
| 28  |
| Countersink Angle:  |
| Between 99.0 degrees and 101.0 degrees                      |
| Material:   |
| Steel comp xm-13  |
| Material Specification:                                     |
| 23-112, type e, cage 76301 mfr ref single material response |
| Surface Treatment:  |
| Passivate   |
| Thread Series Designator:                                   |
| Unjf  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| No  |

## NSN 5305-01-468-9560

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

