NSN 5305-01-469-5718

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-469-5718 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.969 inches and 1.000 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.312 inches and 0.316 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Special Features:** Made to ms16998-74 except finish to be per mil-std 171 - 1.9.2.3 Material: Steel **Surface Treatment:** Zinc alloy and chromate **Surface Treatment Specification:** Astm b633, type ii, class 3 assn standard single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-469-5718

Socket Head Cap Screw - Page 2 of 2



em			

No

Fiig:

A003b0

Mil-std (military Standard):

spec.