

View Online at <https://aerobasegroup.com/nsn/5305-01-470-2440>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.968 inches and 1.000 inches

**Fastener Length:**

0.718 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.122 inches and 0.133 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Screw Material:**

Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1120 or steel comp 1132

**Screw Material Specification:**

Ast-29 federal specification single material response

**Screw Surface Treatment:**

Zinc

**Screw Surface Treatment Specification:**

A astm b633 sc3 type ii federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0