NSN 5305-01-470-6949

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-470-6949 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 0.730 inches and 0.760 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.266 inches and 0.303 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.1900 inches **Grip Length:** Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5000 assn standard single material response and mil-s-6049 assn standard single material response or ams6322 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 assn standard single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas8603 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-470-6949

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.