

View Online at <https://aerobasegroup.com/nsn/5305-01-470-7020>

**Fastener Length:**

Between 1.2032 inches and 1.2968 inches

**Head Style:**

Chamfer flange

**Head Height:**

Between 0.170 inches and 0.190 inches

**Width Between Flats:**

Between 0.305 inches and 0.310 inches

**Extended Washer Diameter:**

Between 0.398 inches and 0.432 inches

**Internal Drive Style:**

Slot

**End Application:**

Radar

**Nonmachine Thread Style:**

Cone point (type bp)

**Nonmachine Thread Diameter:**

0.260 inches

**Special Features:**

Item is a self-tapping, removable, concrete anchor with a specially designed two lead thread, two threads of unequal size, larger diameter thread is notched at intervals along its length to facilitate tapping into masonry materials; a specially-sized carbide-tipped drill bit is supplied with each box of anchors for hole preparation; installation hole should be drilled to not less than one-quarter inch deeper than the anchor penetration into the masonry; the finish has a proprietary synthetic polymer coating; the end item identification is the next generation radar (nexrad), which is used by the national weather service (nws)

**Material:**

Steel comp 1022

**Material Specification:**

Fed-std-66 federal standard single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0