NSN 5305-01-470-9303

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-470-9303

view Offilite at https://aerobasegroup.com/hist//3505-01-4/-0-3505
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.4063 inches and 0.4687 inches
Fastener Length:
Between 1.4063 inches and 1.4687 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.4688 inches and 0.5312 inches
Head Height:
Between 0.1875 inches and 0.2499 inches
Shoulder Diameter:
0.311 inches first shoulder and 0.312 inches first shoulder
Shoulder Length:
0.997 inches first shoulder and 1.003 inches first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
0.156 inches
Thready Qty Per Inch (tpi):
20
Shoulder Shape:
Round first shoulder
Material:
Steel comp 303 or steel comp 304 or steel comp xm-7
Material Specification:
Astm a582/582m assn standard single material response or astm a493 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type ii, type vi or vii federal specification single treatment response
Thread Series Designator:
Unc
Specification Data:
96906-mil-s-51576 government specification
Shelf Life:

N/a

NSN 5305-01-470-9303 Shoulder Screw - Page 2 of 2



	Of			

Demilitarization:

No

Fiig:

A003b0