NSN 5305-01-472-4367

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-472-4367 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** 2.593 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **First Diameter From Head:** 0.250 inches **Second Diameter From Head:** Between 0.170 inches and 0.180 inches **Third Diameter From Head:** 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.213 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: **2.213 inches Internal Drive Style:** Hexagon **End Application:** Bradley **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 20 **Hardness Rating:** 36.0 rockwell c and 45.0 rockwell c **Externally Relieved Body Diameter Quantity:** 3 **Special Features:** Altered from ms16997-69

Material:

Steel

NSN 5305-01-472-4367

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Zinc
Surface Treatment Specification:
Astm a633, type ii, sc2 assn standard single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0