Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-472-4367

• 10	
Th	read Class:
3a	
Th	read Direction:
Rig	ght-hand
Th	read Length:
0.3	380 inches
Fa	stener Length:
2.5	593 inches
Не	ead Style:
Fla	at chamfer
Не	ead Diameter:
Be	tween 0.365 inches and 0.375 inches
He	ead Height:
Be	tween 0.244 inches and 0.250 inches
Fir	rst Diameter From Head:
0.2	250 inches
Se	cond Diameter From Head:
Be	tween 0.170 inches and 0.180 inches
Th	ird Diameter From Head:
0.2	250 inches
Di	stance From Largest Bearing Surface Of Head To End Of First Diameter:
1.2	213 inches
Di	stance From Largest Bearing Surface Of Head To End Of Second Diameter
2.2	213 inches
Int	ernal Drive Style:
He	exagon
En	nd Application:
Bra	adley
Th	read Diameter:
0.2	250 inches
Wi	idth Across Flats:
Be	tween 0.187 inches and 0.190 inches
Th	ready Qty Per Inch (tpi):
20	
На	ardness Rating:
36	.0 rockwell c and 45.0 rockwell c
Ex	ternally Relieved Body Diameter Quantity:
3	
Sp	ecial Features:
Alt	ered from ms16997-69
Ма	aterial:
<u> </u>	

Steel

## NSN 5305-01-472-4367

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:

Zinc

Surface Treatment Specification:

Astm a633, type ii, sc2 assn standard single treatment response

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0