NSN 5305-01-472-5680

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-472-5680 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.325 inches **Fastener Length:** 0.875 inches **Head Style:** Pan **Head Diameter:** Between 0.257 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.090 inches and 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.550 inches **Internal Drive Style:** Cross recess type 1 **End Application:** 5820-01-421-2609 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Special Features:** Altered from ms51957-33 Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 316 or steel comp 316l or steel comp 384 or steel comp xm-7 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-472-5680

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0