

View Online at <https://aerobasegroup.com/nsn/5305-01-472-7167>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.413 inches and 0.438 inches

Fastener Length:

1.063 inches

Head Style:

Knurled no. 1

Head Diameter:

Between 0.419 inches and 0.438 inches

Head Height:

Between 0.209 inches and 0.219 inches

Shoulder Diameter:

0.308 inches all shoulders and 0.310 inches all shoulders

Shoulder Length:

0.625 inches all shoulders

Shoulder Width Across Flats:

0.093 inches all shoulders

Single Shear Strength:

840000 pounds per square inch

Internal Drive Style:

Hexagon

Thread Diameter:

0.312 inches

Width Across Flats:

0.156 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

140000 pounds per square inch

Shoulder Shape:

Round all shoulders

Special Features:

Head plain or knurled is acceptable; see sheet 2 of nasm51975

Color:

Bronze or olive drab

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, typeii, class2 federal specification 1st treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0