## NSN 5305-01-473-0385

Externally Relieved Body Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-473-0385



**Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.115 inches and 0.135 inches **Fastener Length:** 0.312 inches **Head Style:** Pan **Head Diameter:** Between 0.155 inches and 0.181 inches **Head Height:** Between 0.053 inches and 0.062 inches **First Diameter From Head:** Between 0.056 inches and 0.066 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.197 inches **Point Style:** Flat **Internal Drive Style:** Cross recess type 1 **End Application:** 5895-01-435-0571 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 **Material Specification:** Astm a581 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

## NSN 5305-01-473-0385

Externally Relieved Body Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.