## NSN 5305-01-473-1535

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-473-1535 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.200 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.191 inches and 0.225 inches **Internal Drive Style:** Cross recess type 1 **End Application:** F/a-18e/f hornet aircraft **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Criticality Code Justification:** Feat **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Oxide **Shank Surface Treatment Specification:** Mil-c-13924 military specification single treatment response **Special Features:** Essential to weapon system performance or operation, or the preservation of life or safety of operating personnel **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-01-473-1535

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.