NSN 5305-01-473-6247

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-473-6247 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** 1.000 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 55000 pounds per square inch **Screw Material:** Steel comp 1010 or steel comp 1011 or steel comp 1013 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Zinc **Screw Surface Treatment Specification:** Astmb633, type1 assn standard 1st treatment response **Special Features:** This item is made to ms35206-283 with the exception of the protective finish 1.9.2.3 of mil-std-171, except .0003 thick; supplementary chromate treatment to be bronze or olive drab in color **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig: A500d0

No

Demilitarization:

NSN 5305-01-473-6247

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-std-171 spec.