

View Online at <https://aerobasegroup.com/nsn/5305-01-473-6265>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.792 inches and 0.875 inches

Fastener Length:

0.875 inches

Head Style:

Pan

Head Diameter:

Between 0.473 inches and 0.492 inches

Head Height:

Between 0.162 inches and 0.175 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

55000 pounds per square inch

Screw Material:

Steel comp 1010 or steel comp 1011 or steel comp 1013

Screw Material Specification:

66 federal standard all material responses

Screw Surface Treatment:

Zinc

Screw Surface Treatment Specification:

Astmb633, type1 assn standard 1st treatment response

Special Features:

This item is made to ms35206-266 with the exception of the protective finish 1.9.2.3 of mil-std-171, except .0003 thick; supplementary chromate treatment to be bronze or olive drab in color

Thread Series Designator:

Unc

Specification Or Standard:

+2 type and 10p style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-std-171 spec.