

View Online at <https://aerobasegroup.com/nsn/5305-01-473-6265>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.792 inches and 0.875 inches

**Fastener Length:**

0.875 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.473 inches and 0.492 inches

**Head Height:**

Between 0.162 inches and 0.175 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Screw Material:**

Steel comp 1010 or steel comp 1011 or steel comp 1013

**Screw Material Specification:**

66 federal standard all material responses

**Screw Surface Treatment:**

Zinc

**Screw Surface Treatment Specification:**

Astmb633, type1 assn standard 1st treatment response

**Special Features:**

This item is made to ms35206-266 with the exception of the protective finish 1.9.2.3 of mil-std-171, except .0003 thick; supplementary chromate treatment to be bronze or olive drab in color

**Thread Series Designator:**

Unc

**Specification Or Standard:**

+2 type and 10p style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-std-171 spec.