## NSN 5305-01-473-8309

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-473-8309

3a Thread Direction: Right-hand Thread Length: 0.312 inches Fastener Length: Between 0.485 inches and 0.515 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.265 inches and 0.293 inches Head Height: 0.049 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
Right-hand Thread Length: 0.312 inches Fastener Length: Between 0.485 inches and 0.515 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.265 inches and 0.293 inches Head Height: 0.049 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
Thread Length: 0.312 inches Fastener Length: Between 0.485 inches and 0.515 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.265 inches and 0.293 inches Head Height: 0.049 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
0.312 inches Fastener Length: Between 0.485 inches and 0.515 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.265 inches and 0.293 inches Head Height: 0.049 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
Fastener Length:Between 0.485 inches and 0.515 inchesHead Style:Flat countersunk undercutHead Diameter:Between 0.265 inches and 0.293 inchesHead Height:0.049 inchesGrip Diameter:Between 0.1885 inches and 0.1895 inchesSingle Shear Strength:125000 pounds per square inchInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.190 inches
Between 0.485 inches and 0.515 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.265 inches and 0.293 inches Head Height: 0.049 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
Head Style: Flat countersunk undercut Head Diameter: Between 0.265 inches and 0.293 inches Head Height: 0.049 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
Flat countersunk undercut Head Diameter: Between 0.265 inches and 0.293 inches Head Height: 0.049 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
Head Diameter: Between 0.265 inches and 0.293 inches Head Height: 0.049 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
Between 0.265 inches and 0.293 inches Head Height: 0.049 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
Head Height: 0.049 inches Grip Diameter: Between 0.1885 inches and 0.1895 inches Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
0.049 inches <b>Grip Diameter:</b> Between 0.1885 inches and 0.1895 inches <b>Single Shear Strength:</b> 125000 pounds per square inch <b>Internal Drive Style:</b> Offset cruciform (torque set) <b>Thread Diameter:</b> 0.190 inches
Grip Diameter: Between 0.1885 inches and 0.1895 inches Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
Between 0.1885 inches and 0.1895 inches Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
Single Shear Strength: 125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
125000 pounds per square inch Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.190 inches
Offset cruciform (torque set) Thread Diameter: 0.190 inches
Thread Diameter: 0.190 inches
0.190 inches
Grip Length:
Between 0.177 inches and 0.197 inches
Thready Qty Per Inch (tpi):
32
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Nickel alloy 718
Surface Treatment:
Passivate
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0