

View Online at <https://aerobasegroup.com/nsn/5305-01-474-3219>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.235 inches and 0.255 inches

**Fastener Length:**

Between 0.844 inches and 1.156 inches

**Head Style:**

Knurled no. 2

**Head Diameter:**

Between 0.469 inches and 0.781 inches

**Head Height:**

0.250 inches

**Point Length:**

Between 0.110 inches and 0.140 inches

**Point Diameter:**

Between 0.120 inches and 0.130 inches

**First Diameter From Head:**

Between 0.125 inches and 0.135 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.615 inches and 0.635 inches

**Point Style:**

Cone

**Internal Drive Style:**

Slot

**End Application:**

5805-01-452-6730

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Point Chamfer Angle:**

Between 55.0 degrees and 65.0 degrees

**Material:**

Stainless steel

**Material Specification:**

Astma-a-581 assn standard single material response or astma-a582 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0