NSN 5305-01-474-9128

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-474-9128 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.235 inches and 0.265 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.115 inches and 0.125 inches **Locking Feature:** Patch **Internal Drive Style:** High-torque **End Application:** Lau 67 guided missile launcher **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response or ams 5853 assn standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1216 professional/industrial association standard Shelf Life:

Demilitarization: No

Unit Of Measure:

N/a

NSN 5305-01-474-9128

Machine Screw - Page 2 of 2



Fiig:

A500d0