## NSN 5305-01-474-9859

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-474-9859 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.1563 inches and 0.2187 inches **Fastener Length:** Between 0.5283 inches and 0.5967 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.2813 inches and 0.3437 inches **Head Height:** Between 0.1250 inches and 0.1874 inches **Shoulder Length:** 0.372 inches first shoulder and 0.378 inches first shoulder **Shoulder Width Across Flats:** 0.1860 inches first shoulder and 0.1870 inches first shoulder **Internal Drive Style:** Hexagon **End Application:** 5865-01-439-2738 **Thread Diameter:** 0.164 inches Width Across Flats: 0.0940 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Square first shoulder Material: Steel comp 303 **Material Specification:** Astm a582/582m assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type ii federal specification single treatment response **Thread Series Designator:** 

Unc

**Specification Data:** 

96906-ms51576 government standard

## NSN 5305-01-474-9859

Shoulder Screw - Page 2 of 2



-			 
٠.	hΔ	Iŧ.	ife:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0