NSN 5305-01-476-2394

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-476-2394 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.276 inches **Fastener Length:** 1.312 inches **Head Style:** Flat countersunk **Head Diameter:** 0.126 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 591 pounds per square inch **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp 4140 or steel comp 4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, ty2, cl2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1102 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

No

A500d0

NSN 5305-01-476-2394

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.