## NSN 5305-01-477-1206

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-477-1206
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.213 inches and 0.223 inches
Fastener Length:
Between 0.650 inches and 0.665 inches
Head Style:
Pan no. 2
Head Diameter:
0.280 inches
First Diameter From Head:
Between 0.090 inches and 0.095 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.437 inches and 0.442 inches
Internal Drive Style:
Slot
End Application:
Navy equipment
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 304 or steel comp 316
Material Specification:
Qq-s-763 federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Astm a380-88 assn standard single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5305-01-477-1206

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0