
## NSN 5305-01-477-5760

Close Tolerance Screw - Page 1 of 2





**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.573 inches and 0.583 inches Fastener Length: Between 1.698 inches and 1.728 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.749 inches and 0.760 inches **Spline Major Diameter:** Between 0.154 inches and 0.156 inches **Grip Diameter:** 0.374 inches **Point Diameter:** 0.578 inches **Point Style:** Flat **Internal Drive Style:** Torx **Thread Diameter:** 0.375 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degree tension head, gear drive recess **Special Features:** 125 ksi shear strength Material: Nickel alloy 718 **Material Specification:** Ans 5662 assn standard single material response Surface Treatment: Passivate **Thread Series Designator:** 

Unjf

## NSN 5305-01-477-5760

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

