NSN 5305-01-477-5833

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-477-5833 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.464 inches and 0.474 inches **Fastener Length:** Between 1.079 inches and 1.109 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.464 inches and 0.473 inches **Spline Major Diameter:** Between 0.154 inches and 0.156 inches **Grip Diameter:** 0.312 inches **Point Diameter:** 0.469 inches **Point Style:** Flat **Internal Drive Style:** Torx **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degree reduced head, gear drive recess

Special Features: 125 ksi shear strength Material: Stainless steel **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf

NSN 5305-01-477-5833

Close Tolerance Screw - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0