

View Online at <https://aerobasegroup.com/nsn/5305-01-477-7327>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.582 inches

**Fastener Length:**

Between 1.5670 inches and 1.5970 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.573 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**End Application:**

Outboard wing

**Thread Diameter:**

0.3125 inches

**Grip Length:**

Between 0.990 inches and 1.010 inches

**Thready Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Dry film lube (threads only) per mil-I-46010, type i

**Material:**

Cobalt comp mp-35-n

**Material Specification:**

Ams5844 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-I-46010 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-I-46010 spec.