NSN 5305-01-479-1061

Machine Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-01-479-1061



| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.354 inches and 0.384 inches |
| Fastener Length: |
| Between 0.470 inches and 0.500 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.359 inches and 0.385 inches |
| Head Height: |
| 0.116 inches |
| Internal Drive Style: |
| Cross recess type ii |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 1600 pounds per square inch |
| Countersink Angle: |
| Between 80.0 degrees and 82.0 degrees |
| Product Name: |
| Screw, machine, flat countersunk head, 82 degrees, cross-recessed |
| Screw Material: |
| Stainless steel |
| Screw Material Specification: |
| Astm a320 assn standard single material response |
| Screw Surface Treatment Specification: |
| Astm a380, clean and treat assn standard single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A500d0 |
| |