NSN 5305-01-480-0998

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-480-0998

Thread Direction:
Right-hand
Thread Length:
45.3 millimeters
Fastener Length:
50.0 millimeters
Head Style:
Flat countersunk
Head Diameter:
Between 8.9 millimeters and 10.4 millimeters
Head Height:
2.7 millimeters
Internal Drive Style:
Cross recess type 1
End Application:
Light armored vehicle turret support p/n 10604136
Thread Diameter:
5.0 millimeters
Thread Pitch In Millimeters:
0.8
External Thread Tolerance Class:
External Thread Tolerance Class: 6g
6g
6g Countersink Angle:
6g Countersink Angle: 90.0 degrees
6g Countersink Angle: 90.0 degrees Screw Material:
Countersink Angle: 90.0 degrees Screw Material: Steel property class 9.8
Countersink Angle: 90.0 degrees Screw Material: Steel property class 9.8 Screw Surface Treatment:
Countersink Angle: 90.0 degrees Screw Material: Steel property class 9.8 Screw Surface Treatment: Zinc
Countersink Angle: 90.0 degrees Screw Material: Steel property class 9.8 Screw Surface Treatment: Zinc Screw Surface Treatment Specification:
Countersink Angle: 90.0 degrees Screw Material: Steel property class 9.8 Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Astmb633, fe/zn, ty2 assn standard single treatment response
Countersink Angle: 90.0 degrees Screw Material: Steel property class 9.8 Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Astmb633, fe/zn, ty2 assn standard single treatment response Thread Series Designator:
Countersink Angle: 90.0 degrees Screw Material: Steel property class 9.8 Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Astmb633, fe/zn, ty2 assn standard single treatment response Thread Series Designator: M
Countersink Angle: 90.0 degrees Screw Material: Steel property class 9.8 Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Astmb633, fe/zn, ty2 assn standard single treatment response Thread Series Designator: M Shelf Life:
Countersink Angle: 90.0 degrees Screw Material: Steel property class 9.8 Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Astmb633, fe/zn, ty2 assn standard single treatment response Thread Series Designator: M Shelf Life: N/a
Countersink Angle: 90.0 degrees Screw Material: Steel property class 9.8 Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Astmb633, fe/zn, ty2 assn standard single treatment response Thread Series Designator: M Shelf Life: N/a
Countersink Angle: 90.0 degrees Screw Material: Steel property class 9.8 Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Astmb633, fe/zn, ty2 assn standard single treatment response Thread Series Designator: M Shelf Life: N/a Unit Of Measure:
Countersink Angle: 90.0 degrees Screw Material: Steel property class 9.8 Screw Surface Treatment: Zinc Screw Surface Treatment Specification: Astmb633, fe/zn, ty2 assn standard single treatment response Thread Series Designator: M Shelf Life: N/a Unit Of Measure: Demilitarization: