

View Online at <https://aerobasegroup.com/nsn/5305-01-481-7843>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.425 inches

**Fastener Length:**

Between 0.660 inches and 0.690 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.3859 inches and 0.3948 inches

**Spline Minor Diameter:**

Between 0.1105 inches and 0.1125 inches

**Spline Major Diameter:**

Between 0.1540 inches and 0.1560 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Single Shear Strength:**

125000 pounds per square inch

**Point Style:**

Flat

**Internal Drive Style:**

Torx

**End Application:**

F18 e/f

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.240 inches and 0.260 inches

**Features Provided:**

Dry film lubricant

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

4400 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Criticality Code Justification:**

Agav

**Product Name:**

Bolt, 100 degrees reduced head, gear drive recess

**Special Features:**

Cetyl alcohol per mil-I-87132, type i, grade b; chamfered end - chamfer plus incomplete threads not to exceed 2 thread pitches

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629, ph13-8mo assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Mil-dtl-83488, type ii, class 3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-dtl-83488 spec.