## NSN 5305-01-481-9414

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-481-9414 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** 1.594 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.438 inches and 0.445 inches **Spline Major Diameter:** Between 0.154 inches and 0.156 inches **Grip Diameter:** 0.312 inches **Point Diameter:** 0.469 inches **Point Style:** Flat **Internal Drive Style:** Torx **End Application:** F/a-18e, f/a-18f **Thread Diameter:** 0.313 inches **Grip Length:** 1.125 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 5820 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Criticality Code Justification:** Agav **Product Name:** Bolt, 100 degree reduced head, gear drive recess - ph13-8mo (125 ksi shear), inconel 718 (125 ksi shear), 6al-4v titanium (95 ksi shear). Material: Steel comp xm-13 **Surface Treatment:** 

**Passivate** 

## NSN 5305-01-481-9414

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0