## NSN 5305-01-482-2898



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-482-2898 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** Between 0.497 inches and 0.500 inches **Head Style:** Round extended washer **Head Diameter:** 0.353 inches **Head Height:** Between 0.085 inches and 0.105 inches **Extended Washer Diameter:** 0.428 inches **Extended Washer Thickness:** Between 0.030 inches and 0.037 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Screw Material:** Steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, tyii, cl2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:** 

## NSN 5305-01-482-2898

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.