

View Online at <https://aerobasegroup.com/nsn/5305-01-482-3277>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.210 inches

**Fastener Length:**

0.830 inches

**Head Style:**

Dished hexagon

**Head Height:**

0.250 inches

**Width Between Flats:**

Between 0.1875 inches and 0.1900 inches

**Hole Diameter:**

0.052 inches

**Point Diameter:**

0.185 inches

**First Diameter From Head:**

0.185 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.370 inches

**Point Style:**

Flat

**Internal Drive Style:**

Hexagon

**End Application:**

Mk95mod1, moun

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

0.185 inches

**Hole Quantity:**

2

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Hole Configuration Style:**

Hexagon flats

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Item is altered from part number ms16995-49. Locking hole is drilled into side of head, through internal drive and out the other side of head

**Color:**

Black

**Material:**

Steel comp 304

**Material Specification:**

Astmf593 assn standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, class4 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.