NSN 5305-01-482-3277

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-482-3277 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.210 inches **Fastener Length:** 0.830 inches **Head Style:** Dished hexagon **Head Height:** 0.250 inches Width Between Flats: Between 0.1875 inches and 0.1900 inches **Hole Diameter:** 0.052 inches **Point Diameter:** 0.185 inches First Diameter From Head: 0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.370 inches **Point Style:** Flat **Internal Drive Style:** Hexagon **End Application:** Mk95mod1, moun **Thread Diameter:** 0.250 inches Width Across Flats: 0.185 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 20 **Hole Configuration Style:** Hexagon flats

1

Externally Relieved Body Diameter Quantity:

NSN 5305-01-482-3277

Externally Relieved Body Screw - Page 2 of 2



Special Features:
Item is altered from part number ms16995-49. Locking hole is drilled into side of head, through internal drive and out the other side of head
Color:
Black
Material:
Steel comp 304
Material Specification:
Astmf593 assn standard single material response
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924, class4 military specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.

Demilitarization: