Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-482-3277

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.210 inches
Fastener Length:
0.830 inches
Head Style:
Dished hexagon
Head Height:
0.250 inches
Width Between Flats:
Between 0.1875 inches and 0.1900 inches
Hole Diameter:
0.052 inches
Point Diameter:
0.185 inches
First Diameter From Head:
0.185 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.370 inches
Point Style:
Flat
Internal Drive Style:
Hexagon
End Application:
Mk95mod1, moun
Thread Diameter:
0.250 inches
Width Across Flats:
0.185 inches
Hole Quantity:
2
Ноје Туре:
Drilled
Thready Qty Per Inch (tpi):
20
Hole Configuration Style:
Hexagon flats
Externally Relieved Body Diameter Quantity:
1



Special Features:

Item is altered from part number ms16995-49. Locking hole is drilled into side of head, through internal drive and out the other side of head **Color:**

Black

Material:

Steel comp 304

Material Specification:

Astmf593 assn standard single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, class4 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.