NSN 5305-01-483-3048

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-483-3048 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 0.323 inches and 0.353 inches **Head Style:** Pan **Head Diameter:** Between 0.309 inches and 0.331 inches **Head Height:** Between 0.088 inches and 0.102 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Offset cruciform (torque set) **End Application:** C-295 acft **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a

__

Unit Of Measure:

NSN 5305-01-483-3048

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0