NSN 5305-01-483-4773

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-483-4773 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 1.322 inches and 1.338 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **End Application:** Support or pre-provisioning items for which navicp-phil acts as poe **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 32 **Criticality Code Justification: Product Name:** Bolt, pan head, close tolerance, short thread, cruciform recess, titanium alloy gal-4v, self-locking and nonlocking Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard 1st material response or ams 4967 assn standard 2nd material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas 4006 assn standard single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5305-01-483-4773

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0