Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-484-0091

Thread Clas	SS:
2a	
Thread Dire	ection:
Right-hand	
Thread Len	gth:
Between 0.1	78 inches and 0.198 inches
Fastener Le	ength:
0.625 inches	3
Head Style:	
Pan	
Head Diame	eter:
Between 0.2	256 inches and 0.294 inches
Head Heigh	t:
Between 0.0	087 inches and 0.097 inches
First Diame	ter From Head:
Between 0.0	090 inches and 0.100 inches
Distance Fr	om Largest Bearing Surface Of Head To End Of First Diameter:
0.437 inches	5
Internal Driv	ve Style:
Cross reces	s type 1
End Applica	ation:
On486/usm6	536, cass
Thread Diar	meter:
0.138 inches	5
Thready Qt	y Per Inch (tpi):
32	
Externally F	Relieved Body Diameter Quantity:
1	
Material:	
Steel comp	302 or steel comp 303 or steel comp 304
Surface Tre	patment:
Passivate	
Surface Tre	eatment Specification:
Mil-f-14072-	c, type i military specification single treatment response
Thread Seri	ies Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Mea	isure:
 Demilitariza	ation:

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-f-14072-c spec.