## NSN 5305-01-484-0094

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-484-0094 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.178 inches and 0.198 inches **Fastener Length:** 0.688 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.294 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches **Internal Drive Style:** Cross recess type 1 **End Application:** On486/usm636, cass **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072-c, type i military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-01-484-0094

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072-c spec.