## NSN 5305-01-484-0118

Thumbscrew - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-484-0118

| Thread Class:  |
|--|
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.490 inches and 0.510 inches  |
| Fastener Length:   |
| Between 0.490 inches and 0.510 inches  |
| Head Style:  |
| Knurled no. 2  |
| Head Diameter:   |
| Between 0.375 inches and 0.395 inches  |
| Head Height:   |
| Between 0.300 inches and 0.330 inches  |
| End Application:   |
| On486/usm636, cass   |
| Thread Diameter:   |
| 0.138 inches   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Product Name:  |
| Navy special project   |
| Material:  |
| Steel comp 303   |
| ·  |
| Material Specification:  |
|  |
| Material Specification:  |
| Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response   |
| Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment:  |
| Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate  |
| Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:   |
| Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-356, type ii federal specification single treatment response   |
| Material Specification:  Astm a581 assn standard single material response or astm 582-95 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-356, type ii federal specification single treatment response  Thread Series Designator:   |
| Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-356, type ii federal specification single treatment response Thread Series Designator: Unc   |
| Material Specification:  Astm a581 assn standard single material response or astm 582-95 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-356, type ii federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:                                     |
| Material Specification:  Astm a581 assn standard single material response or astm 582-95 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-356, type ii federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a                                |
| Material Specification:  Astm a581 assn standard single material response or astm 582-95 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-356, type ii federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a                                |
| Material Specification:  Astm a581 assn standard single material response or astm 582-95 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-356, type ii federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a  Unit Of Measure:              |
| Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-356, type ii federal specification single treatment response  Thread Series Designator: Unc  Shelf Life: N/a  Unit Of Measure: Demilitarization: |