NSN 5305-01-484-0118

Thumbscrew - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-484-0118

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.490 inches and 0.510 inches
Fastener Length:
Between 0.490 inches and 0.510 inches
Head Style:
Knurled no. 2
Head Diameter:
Between 0.375 inches and 0.395 inches
Head Height:
Between 0.300 inches and 0.330 inches
End Application:
On486/usm636, cass
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Product Name:
Navy special project
Material:
Steel comp 303
·
Material Specification:
Material Specification:
Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response
Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment:
Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate
Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-356, type ii federal specification single treatment response
Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-356, type ii federal specification single treatment response Thread Series Designator:
Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-356, type ii federal specification single treatment response Thread Series Designator: Unc
Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-356, type ii federal specification single treatment response Thread Series Designator: Unc Shelf Life:
Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-356, type ii federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a
Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-356, type ii federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a
Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-356, type ii federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:
Material Specification: Astm a581 assn standard single material response or astm 582-95 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-356, type ii federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: