NSN 5305-01-484-7554

Machine Screw - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5305-01-484-7554

3a					
Thread Direction:					
Right-hand					
Thread Length:					
Between 0.782 inches and 0.875 inches					
Fastener Length:					
Between 0.969 inches and 1.000 inches					
Head Style:					
Fillister					
Head Diameter:					
Between 0.306 inches and 0.313 inches					
Head Height:					
Between 0.103 inches and 0.118 inches					
Hole Diameter:					
Between 0.034 inches and 0.042 inches					
Internal Drive Style:					
Torque set					
Thread Diameter:					
0.190 inches					
Hole Quantity:					
1					
Thready Qty Per Inch (tpi):					
32					
Min. Tensile Strength (psi):					
160000 pounds per square inch					
Screw Material:					
Iron alloy 660					
Screw Material Specification:					
Ams 5737 assn standard single material response					
Screw Surface Treatment:					
Passivate					
Screw Surface Treatment Specification:					
Qq-p-35 federal specification single treatment response					
Head Hole Configuration Style:					
Round					
Bearing Surface Of Head Surface Finish:					
32.0 microinches					
Thread Surface Finish:					
32.0 microinches					
Thread Series Designator:					
Unjf					

NSN 5305-01-484-7554

Machine Screw - Page 2 of 2



~n	ΔC IT	100	HINE	1 1 1	212
JU	CUII	166	ıtior	·	ala.

80205-nas1101 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0