NSN 5305-01-484-7554

Machine Screw - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5305-01-484-7554

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.782 inches and 0.875 inches
Fastener Length:
Between 0.969 inches and 1.000 inches
Head Style:
Fillister
Head Diameter:
Between 0.306 inches and 0.313 inches
Head Height:
Between 0.103 inches and 0.118 inches
Hole Diameter:
Between 0.034 inches and 0.042 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.190 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Head Hole Configuration Style:
Round
Bearing Surface Of Head Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjf

NSN 5305-01-484-7554

Machine Screw - Page 2 of 2



\r		•	C 2 t	ınn	11212	Į
OL.	, .		Cal	UII	Data	,

80205-nas1101 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0