

View Online at <https://aerobasegroup.com/nsn/5305-01-485-5025>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.302 inches

**Fastener Length:**

1.375 inches

**Head Style:**

Flat fillister

**Head Diameter:**

Between 0.550 inches and 0.562 inches

**Head Height:**

Between 0.368 inches and 0.375 inches

**Internal Drive Style:**

Hexagon

**End Application:**

Eots offload; consolidated automated support system

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

Between 0.312 inches and 0.316 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell b

**Minimum Yield Strength:**

30000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Product Name:**

Screw, captive

**Special Features:**

Make from nas1352c6-24

**Material:**

Stainless steel

**Material Specification:**

Nas1352c national specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0